UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/797,925	03/10/2004	Andreas Lopp	SANZ-253	3357
	7590 09/03/200 & JAWORSKI, LLP	8	EXAMINER	
666 FIFTH AV	E		BAND, MICHAEL A	
NEW YORK, NY 10103-3198			ART UNIT	PAPER NUMBER
			1795	
			MAIL DATE	DELIVERY MODE
			09/03/2008	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)
	10/797,925	LOPP ET AL.
Office Action Summary	Examiner	Art Unit
	MICHAEL BAND	1795
The MAILING DATE of this communication ap Period for Reply	ppears on the cover sheet with the	correspondence address
A SHORTENED STATUTORY PERIOD FOR REP WHICHEVER IS LONGER, FROM THE MAILING I - Extensions of time may be available under the provisions of 37 CFR 1 after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory perio - Failure to reply within the set or extended period for reply will, by statu. Any reply received by the Office later than three months after the mail earned patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMUNICATION 1.136(a). In no event, however, may a reply be tind will apply and will expire SIX (6) MONTHS from the, cause the application to become ABANDONE	N. mely filed I the mailing date of this communication. ED (35 U.S.C. § 133).
Status		
1) Responsive to communication(s) filed on 04.	nis action is non-final. vance except for formal matters, pro	
Disposition of Claims		
4) Claim(s) 1-18 is/are pending in the applicatio 4a) Of the above claim(s) is/are withdr 5) Claim(s) is/are allowed. 6) Claim(s) 1-18 is/are rejected. 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and/ Application Papers 9) The specification is objected to by the Examir 10) The drawing(s) filed on 12 July 2007 is/are: a	rawn from consideration. /or election requirement.	by the Examiner.
Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the E	e drawing(s) be held in abeyance. Se ection is required if the drawing(s) is ob	e 37 CFR 1.85(a). ejected to. See 37 CFR 1.121(d).
Priority under 35 U.S.C. § 119		
 12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of: 1. Certified copies of the priority document 2. Certified copies of the priority document 3. Copies of the certified copies of the priority application from the International Bure * See the attached detailed Office action for a list 	nts have been received. nts have been received in Applicat iority documents have been receiv au (PCT Rule 17.2(a)).	ion No ed in this National Stage
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date	4) Interview Summary Paper No(s)/Mail D 5) Notice of Informal F 6) Other:	ate

DETAILED ACTION

Continued Examination Under 37 CFR 1.114

1. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 8/4/2008 has been entered.

Drawings

2. The drawings are objected to under 37 CFR 1.83(a) because they fail to show part [W] as described in the specification. Any structural detail that is essential for a proper understanding of the disclosed invention should be shown in the drawing. MPEP § 608.02(d). Corrected drawing sheets in compliance with 37 CFR 1.121(d) are required in reply to the Office action to avoid abandonment of the application. Any amended replacement drawing sheet should include all of the figures appearing on the immediate prior version of the sheet, even if only one figure is being amended. The figure or figure number of an amended drawing should not be labeled as "amended." If a drawing figure is to be canceled, the appropriate figure must be removed from the replacement sheet, and where necessary, the remaining figures must be renumbered and appropriate changes made to the brief description of the several views of the drawings for consistency. Additional replacement sheets may be necessary to show the renumbering

Art Unit: 1795

of the remaining figures. Each drawing sheet submitted after the filing date of an application must be labeled in the top margin as either "Replacement Sheet" or "New Sheet" pursuant to 37 CFR 1.121(d). If the changes are not accepted by the examiner, the applicant will be notified and informed of any required corrective action in the next Office action. The objection to the drawings will not be held in abeyance.

Claim Rejections - 35 USC § 103

- 3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 4. Claims 1-7, 9-15, and 17-18 are rejected under 35 U.S.C. 103(a) as being unpatentable over Morrison, Jr. (US Patent No. 4,461,688) in view of Lehan (WO 96/21750) and Hughes et al (US Patent No. 5,873,989).

With respect to claim 1, Morrison discloses a magnetron and target (abstract, lines 1-2; fig. 5, [12]) with the magnetron comprising a magnet system with at least one inner magnet and at least one outer magnet (fig. 5, [46'], [52']). This magnet system forms at least one closed plasma tube (i.e. plasma loop or plasma path) between an inner and outer magnet (abstract, lines 10-14 and lines 19-20). Between the inner and outer magnets, there exist two regions at a distance (i.e. C) from one another as evidenced by the space between either S and N poles or N and N poles (fig 5).

Art Unit: 1795

However Morrison is limited in that there is no description or illustration to display the shape of the plasma tube.

Lehan displays a plasma racetrack (i.e. tube) (fig. 2B) schematically similar in design to applicant with dimensions " W_L " (i.e. "d") and " D_P " (i.e. "B"/2). This type of design reduces erosion of a target at the end portions while the magnetic field at the ends need not be significantly reduced, leading to maintained efficiency of magnetron (abstract).

It would have been obvious to one of ordinary skill in the art to use the plasma racetrack taught in Lehan as the plasma tube in Morrison in order to gain the advantages of reduced erosion of the end portions of target while not reducing the magnetic field and thus, maintaining magnetron efficiency and one of ordinary skill would have a reasonable expectation of success in making such a modification.

However modified Morrison is further limited in that the magnets do not move linearly over the target.

Hughes et al teaches a sputtering magnetron contained inside a vacuum chamber capable of moving linearly across a target at a distance (i.e. W) and utilizing a plasma tube. The abstract discloses "a magnet assembly disposed in proximity of the target" (abstract, lines 3-4) and "a drive assembly for scanning (i.e. moving) the magnet assembly relative to the target" (abstract, lines 5-6) in order for the magnet to sputter more of the target area.

It would have been obvious to one of ordinary skill in the art at the time of the invention to use a moving magnetron relative to target and plasma race-track taught in Hughes et al as part of the sputtering magnetron apparatus in Morrison '688 in order to

gain the advantages of increased efficiency in uniform erosion of the target well known in the art and one of ordinary skill in the art would have a reasonable expectation of success in making such a modification.

With respect to claim 2, Morrison discloses a magnetron and target (abstract, lines 1-2; fig. 5, [12]) with the magnetron comprising a magnet system with at least one inner magnet and at least one outer magnet (fig. 5, [46'], [52']). This magnet system forms at least one closed plasma tube (i.e. plasma loop or plasma path) between an inner and outer magnet (abstract, lines 10-14 and lines 19-20). Between the inner and outer magnets, there exist two regions at a distance (i.e. C) from one another as evidenced by the space between either S and N poles or N and N poles (fig. 5). However Morrison is limited in that there is no description or illustration to display the shape of the plasma tube.

Lehan displays a plasma racetrack (i.e. tube) (fig. 2B) schematically similar in design to applicant with dimensions "W_L" (i.e. "d") and "D_P" (i.e. "B"/2). This type of design reduces erosion of a target at the end portions while the magnetic field at the ends need not be significantly reduced, leading to maintained efficiency of magnetron (abstract). Since "B" was obviously less than "d" as discussed, "B" greater than or equal to "2d" must hold true if both "B" and "d" are greater than one.

It would have been obvious to one of ordinary skill in the art to use the plasma racetrack taught in Lehan as the plasma tube in Morrison in order to gain the advantages of reduced erosion of the end portions of target while not reducing the magnetic field and thus, maintaining magnetron efficiency and one of ordinary skill would have a reasonable expectation of success in making such a modification.

Art Unit: 1795

However modified Morrison is further limited in that the magnets do not move over the target.

Hughes et al teaches a sputtering magnetron contained inside a vacuum chamber capable of moving linearly across a target at a distance (i.e. W) and utilizing a plasma tube. The abstract discloses "a magnet assembly disposed in proximity of the target" (abstract, lines 3-4) and "a drive assembly for scanning (i.e. moving) the magnet assembly relative to the target" (abstract, lines 5-6) in order for the magnet to sputter more of the target area.

It would have been obvious to one of ordinary skill in the art at the time of the invention to use a moving magnetron relative to target and plasma race-track taught in Hughes et al as part of the sputtering magnetron apparatus in Morrison in order to gain the advantages of increased efficiency in uniform erosion of the target well known in the art and one of ordinary skill in the art would have a reasonable expectation of success in making such a modification.

With respect to claims 3 and 11, modified Morrison further discloses fig. 11 having magnetic fields A and B. In between A and B, two significantly smaller fields are seen. There exists a certain distance between parts [120]/[132] and parts [108]/[130] (i.e. distance C) that separates the two. The horizontal midpoint of each white space between parts [120]/[132] and parts [108]/[130] represents the endpoints of the certain distance (i.e. distance C). According to the drawing, the magnetic fields present in fig. 11 are similar to the fields depicted in the application drawings. In fig. 11 it appears that at either contrived endpoint, the component of the magnetic field perpendicular to the surface of the target is zero.

With respect to claims 4 and 12, modified Morrison further discloses fig. 11 that has smaller magnetic fields between magnetic fields A and B, forming a semi-oval from the points at which the smaller magnetic fields intersect the target. Fig. 3 displays prior art with a schematically similar magnetic arrangement as that of Morrison. The acute angle present is 45°. However Morrison is limited in that fig. 3 displays an angle of 45°, while applicant claims an angle of 20°.

It has been held that where the only difference between the prior art and the claims was a recitation of relative dimensions of the claimed device and a device having the claimed relative dimensions would not perform differently than the prior art device, the claimed device was not patentably distinct from the prior art device. Gardner v. TEC Systems, Inc., 725 F.2d 1338, 220 USPQ 777 (Fed. Cir. 1984), cert. denied, 469 U.S. 830, 225 USPQ 232 (1984).

Therefore it would have been obvious to one of ordinary skill in the art to have the magnetic field form a plurality of angles, including 20° and 45°, and one of ordinary skill would have a reasonable expectation of success in making the modification.

With respect to claims 5 and 13, modified Morrison further discloses a "closed plasma loop" (abstract; col. 7, lines 61-68; col. 8, lines 1-9) that is schematically similar to the plasma tube described by application. From fig. 11, the smaller magnetic fields between magnetic fields A and B, a semi-oval is formed from the points at which the smaller magnetic fields intersect the target. The angles formed from these intersections are acute angles. Fig. 2 in Morrison displays the magnetic field forming an angle of 45° with that of the target. However modified Morrison is limited in that figure 2 displays an angle of 45°, while applicant claims an angle of 20°.

It has been held that where the only difference between the prior art and the claims was a recitation of relative dimensions of the claimed device and a device having the claimed relative dimensions would not perform differently than the prior art device, the claimed device was not patentably distinct from the prior art device. Gardner v. TEC Systems, Inc., 725 F.2d 1338, 220 USPQ 777 (Fed. Cir. 1984), cert. denied, 469 U.S. 830, 225 USPQ 232 (1984).

Therefore it would have been obvious to one of ordinary skill in the art to have the magnetic field form a plurality of angles, including 20° and 45°, and one of ordinary skill would have a reasonable expectation of success in making the modification.

With respect to claims 6 and 14, Hughes et al further discloses that the magnet assembly that "is linearly scanned (i.e. moved) by the drive assembly along a scan direction relative to target" (col. 3, lines 1-2). "The magnet assembly is scanned with a reciprocating linear movement and changes direction at or near opposite edges of the target" (col. 5, 63-65).

With respect to claims 7 and 15, modified Morrison further discloses fig. 10 which has a long bar magnet on the outsides (fig. 10, [108], [120]) with a short magnet at the ends (fig. 10, [110], [112], [122], [124]) as a "roof". A smaller bar magnet is on the inside (fig. 10, [130], [132]). The closed plasma loops run between the smaller bar magnets and the long bar magnets with "roofs" as evidenced by fig. 11.

With respect to claims 9 and 17, modified Morrison further depicts fig. 11 having similar types of magnets (i.e. small and long magnets) that form two distinct outer regions, with one part of the first region composing the second region and vice versa. The two regions also have an inner magnet with the outer boundary being composed of

an arrangement of long and short magnet bars. Morrison further depicts fig. 13 having a comparable shape with the plasma tubes sharing a boundary that separates the two tubes. However modified Morrison is limited in that the magnets only contain 2 tubes instead of 3 tubes.

Although the reference does not disclose three tubes, it has been held that the mere duplication of parts has no patentable significance unless a new and unexpected result is produced. *In re Harza*, 274 F.2d 669, 124 USPQ 378 (CCPA 1960).

Therefore it would have been obvious to one of ordinary skill in the art to duplicate the closed plasma loop any number of times in order to increase efficiency in uniform target erosion, increase film uniformity thickness onto substrate, increase overall target area sputtered, and decrease overall amount of sputtering time needed per substrate and one of ordinary skill would have a reasonable expectation of success in making the modification.

With respect to claims 10 and 18, modified Morrison further depicts fig. 10 having the outer magnets (fig. 10, [108], [114], [116], [120], [126], [128]) as all being parallel, with parts [114], [116], [126], [128] being shorter than parts [108] and [120]. Fig. 10 further depicts that the ends of the two magnets are connected with one another by an L-form magnet configuration, for example, figure 10, parts [126] and [122].

5. Claims 8 and 16 are rejected under 35 U.S.C. 103(a) as being unpatentable over Morrison, Jr. (US Patent No. 4,461,688), Lehan (WO 96/21750), and Hughes et al (US Patent No. 5,873,989) as applied to claims 7 and 15 above, and further in view of Tsukasa (JP No. 10088339).

Art Unit: 1795

With respect to claims 8 and 16, the references are cited as discussed for claims 1, 2, 7 and 15. Modified Morrison depicts fig. 10 as having the inner magnet a prism shape. However modified Morrison is limited in that the entire inner magnet is of a uniform length and width instead of having a smaller diameter at its ends than its center.

Tsukasa teaches an inner magnet [70] that has a smaller diameter at the point than in the center. The inside magnet is rectangular until reference point A1, at which the magnet becomes smaller than the center part. This enhances the availability of a target "by making the cross-sectional area of erosion in the vicinity of both edge parts in the longitudinal direction not larger than the cross-sectional area of erosion in the center part in the longitudinal direction in the cross-sectional area of erosion in the reciprocating direction of a magnet unit" (abstract).

It would have been obvious to one of ordinary skill in the art to use the inner magnets taught in Tsukasa as the inner magnet for the plasma track in Morrison in order to gain the advantage of improved availability of a target well known in the art and one of ordinary skill would have a reasonable expectation of success in making such a modification.

Response to Arguments

6. Applicant's arguments filed 8/4/2008 have been fully considered but they are not persuasive.

103 Rejections

Art Unit: 1795

7. On p. 7-9, the Applicant argues that Morrison fails to disclose a magnetron and target capable of being moved relative to each other. The Applicant also argues that Morrison fails to disclose an inner magnet and an outer magnet. The Applicant also argues that Morrison fails to teach the claimed limitation of a distance C in addition to other regions at a distance of C.

The Examiner respectfully disagrees with regards to Morrison not disclosing an inner magnet and outer magnets. Fig. 5 does depict an inner magnet [52'] and an outer magnet [46], as the Examiner stated in the rejections of claims 1-2 above. With regards to a magnetron and target moving linearly, the Examiner has admitted that Morrison does not disclose this limitation. However the Examiner has combined Morrison with Hughes et al since Hughes et al does teach linear movement relative to a target and magnetron, with proper motivation for this combination given above. With regards to the limitations of C, the Examiner has admitted that Morrison does not disclose these limitations. However the Examiner has combined Morrison with Lehan et al since Lehan et al teaches a plasma racetrack (i.e. tube) similar to one that would be formed by Morrison and both references teach using outer and inner magnets. The Examiner admits that Lehan et al and Morrison teach different magnetrons, however both teach having a plasma tube or racetrack, thus it is obvious to one of ordinary skill in the art that the plasma racetrack parameters as specified by Lehan et al are applicable to the plasma tube of Morrison.

Art Unit: 1795

Conclusion

8. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Michael Band whose telephone number is (571) 272-9815. The examiner can normally be reached on Mon-Fri, 8am-4pm, EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Alexa Neckel can be reached on (571) 272-1446. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

9. Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/M. B./

Examiner, Art Unit 1795

/Alexa D. Neckel/

Supervisory Patent Examiner, Art Unit 1795